SOLAR SYNC® FEATURES & SPECIFICATIONS

Features

- Provides automatic daily adjustment to program run times
- · Wired and wireless models available
- · Rain and freeze shutoff
- · Gutter mount bracket included
- · Warranty period: 5 years (10 year battery warranty for wireless model)

Specifications

- Maximum distance sensor to module: 200 ft. (wired model) or 800 ft. (wireless model)
- 40 ft. of wire included in kit (wired model)
- · Solar Sync and Wireless Solar Sync compatible with Pro-C 300 and PCC controllers
- · Solar Sync Sensor and Wireless Solar Sync Sensor are compatible with X-Core, new Pro-C 400/PCC Series, I-Core, and ACC controllers

Model

Smart, weather-based controls are available in every Hunter AC powered controller.

SOLAR SYNC SENSOR

(with mounting arm)

Height: 3" Width: 81/2" Depth: 1"



SOLAR SYNC MODULE

Height: 13/4" Width: 5" Depth: 3/4"



WIRELESS SOLAR SYNC SENSOR

(with mounting arm)

Height: 41/2" Width: 81/2" Depth: 1"



WIRELESS SOLAR SYNC RECEIVER

Height: 51/2" Width: 11/2" Depth: 11/2"



SOLAR SYNC MODEL CHART Model Description Solar Sync kit for use with PCC and Pro-C 300 controllers. Includes Solar Sync Sensor and module. SOLAR SYNC Wired Solar Sync for use with ACC, I-Core, New Pro-C 400/PCC Series, and X-Core controllers. Includes Solar Sync SOLAR SYNC-SEN Wireless Solar Sync for use with PCC and Pro-C 300 controllers. Includes Wireless Solar Sync Sensor, Wireless WSS receiver, and module. Wireless Solar Sync for use with ACC, I-Core, new Pro-C 400/PCC Series, and X-Core controllers. Includes wireless WSS-SEN Solar Sync Sensor and wireless receiver.

Website hunterindustries.com | Customer Support 1-800-383-4747 | Technical Service 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

